

## JCU-500A Digital Camera Main Machine

- Mix Discussion, camera tracking and voting functions together.
- Professional digital USB MP3 play and RECORDER.
- Teleconferencing is allowed with telephone coincidence.
- Built in frequency shifting, restraining screaming.
- The rack hole: fixed the main machine in the 19" standard rack.
- Holder Camera Setting: bring about the function, still tracking even breaking videography.
- Tracking blackout remembering function, still tracking even breaking away from a computer.
- The main machine has 3 route can connect 60 units, through extend power can connect 120 units.
- Seceding the computer and controlling the keyboard could bring about the function of automatic tracking videography.
- LCD display screen meny of English, Bring about the control of the meeting function with the function-key.
- Seceding computer, still having the following mode:
  - Free discussion model,turn on the unit or units (no limited) in arbitrary at the same times.
  - Amount limited model : turn on the unit with 1/2/3/4/5/6 at the same time.
  - FIFO model: speaking units 1/2/3/4/5/6 can be controlled.
  - Chairman mode: only allows the chairman to speak.

## JCU-501C/D Chairman & Delegate

- Match with 2.1M connection cable.
- Through branching unit to hand in hand connected each unit.
- With 5 button voting, Yes , No , Abstain , Reset, Attend .
- With two microphone input design (adding the lapel microphone hub)
- Inside work with DC24V power by Main Machine, It's saftey for users.
- Loudspeaker with auto mute, earphone jack and volume adjusting knob.
- Chairman unit with priority speaking, can off each representative speaking unit.
- Chairmen can shut down all delegates, and chairmen do not be limited by main machine.
- Unit-direction condenser microphone: gooseneck microphone with green ring indicator LED.
- Open the microphone automatically mute speakers with headphone jack and volume control knob.
- With the 160x32 LCD display screen menu of English and showing the meeting information and state of the equipment.
- JCU-500A Main Machine

input/output	8P-DIN x 4
input	MIC 6.3mm x 1 RCA x 2
output	XLRM x 1 (BL) RCA x 1
power supply	AC220V-50Hz
current drain	120W (MAX)
frequency resonance	100-14KHz
dimension	480x325x88mm
weight	8.5KG
colors	Dark Gray

- JCU-510C/D MIC UNIT

input/output	8P-DIN x 1 (2M)
input	Condenser Microphone
power supply	DC24V
current drain	40mA
sensitivity	-47Db
s/n	65Db
frequency resonance	100-10KHz
weight	1.4 KG
colors	Silver/Gray Black
installation	Desktop
MIC Stem Length	400mm (Activity)